KIPac

Keel Support Keel Support F-Series 1.5 T - 10 T

Our F-Series Adjustable Height Keel Supports are designed for the safe and convenient storage of boats, offering a holding capacity of up to 10,000 kg. Constructed from high-quality materials and coated with a durable finish, these keel supports withstand challenging marine environments and provide long-lasting support for your boat.

Safety is a top priority in the design of our keel supports. The hull pads provide a stable platform for secure storage, preventing your boat from shifting or moving while in storage. Independently tested and certified, our keel supports can safely support a working load of up to 10,000 kg.

Our keel supports are easy to use and customizable to accommodate a wide range of hull configurations. Simply drive your boat onto the keel support and secure it in place. The adjustable hull pads feature a vertical base and a swivelling top up to 25°, ensuring a snug fit for various hull shapes. Constructed from durable materials and coated with a corrosion-resistant finish, our F-Series Keel Supports deliver exceptional performance in challenging maritime conditions.

Key Features:

- » Holding capacity up to 10,000 kg, suitable for a variety of boats
- » Accommodates a wide range of hull configurations for versatile support
- » Hull pads with a vertical base and swivelling top up to 25° adapt to various hull shapes
- » Telescopic supports with precise height control for a customized fit
- » Hull pad size of 120 x 250 mm, ensuring adequate support
- » Adaptable for use on a variety of surfaces, including dirt, gravel, cement, and asphalt
- » Provides exceptional stability and security during boat storage

Durable Protective Coatings:

- » Powder Coating
- » Hot Dip Galvanizing
- » High-Quality Paint Finish



Adjustable height keel support for easy and secure boat storage.



Dimension:

| Capacity: | Width: | Height: | | | Capacity: | Width: | Height: | |
|-----------|---------|---------|---------|---|-----------|---------|---------|---------|
| | | Min: | Max: | | | | Min: | Max: |
| 1.5 T | 850 mm | 600 mm | 1000 mm | | 6 T | 850 mm | 600 mm | 1000 mm |
| 1.5 T | 850 mm | 800 mm | 1200 mm | | 6 T | 850 mm | 800 mm | 1200 mm |
| 1.5 T | 850 mm | 1000 mm | 1400 mm | | 6 T | 850 mm | 1000 mm | 1400 mm |
| 1.5 T | 1050 mm | 600 mm | 1000 mm | | 6 T | 1050 mm | 600 mm | 1000 mm |
| 1.5 T | 1050 mm | 800 mm | 1200 mm | _ | 6 T | 1050 mm | 800 mm | 1200 mm |
| 1.5 T | 1050 mm | 1000 mm | 1400 mm | _ | 6 T | 1050 mm | 1000 mm | 1400 mm |
| | | | | | | | | |
| 3.5 T | 850 mm | 600 mm | 1000 mm | - | 10 T | 850 mm | 600 mm | 1000 mm |
| 3.5 T | 850 mm | 800 mm | 1200 mm | - | 10 T | 850 mm | 800 mm | 1200 mm |
| 3.5 T | 850 mm | 1000 mm | 1400 mm | - | 10 T | 850 mm | 1000 mm | 1400 mm |
| 3.5 T | 1050 mm | 600 mm | 1000 mm | - | 10 T | 1050 mm | 600 mm | 1000 mm |
| 3.5 T | 1050 mm | 800 mm | 1200 mm | - | 10 T | 1050 mm | 800 mm | 1200 mm |
| 3.5 T | 1050 mm | 1000 mm | 1400 mm | - | 10 T | 1050 mm | 1000 mm | 1400 mm |
| | | | | | | | | |

* We can customize our products to fit your specific width, height, and capacity requirements.

The dimensions of tubular profiles, square profiles, threaded rod bars, and heavy-duty wheels change depending on the size and capacity of the products. We use high-quality materials, such as S235, S275, and S355, high-strength structural steels certified for their origin. To ensure the safety and quality of our products, we obtain a CE mark certificate for each one.

35 - -